



VOLT SB FO E PS HRO SR

HRD055H

CE EN ISO 20345:2022 SB FO E PS HRO SR

LOW SAFETY SHOE

39-47

DIELECTRIC Sole line

Low safety shoe, suede back leather thickness 1,8-2,0 mm.
External 3D fabric, perspiring and abrasion resistant.
Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite **non-thermic** according to EN 22568

PS MIDSOLE fabric INSULATION composite flexible anti-perforation according to EN 22568

SOLE HARD ROCK INSULATING bidensity polyurethane and **INSULATING RUBBER** resistant to hydrocarbons and to abrasion, anti-shock and anti-slipping
Article HRD055H has been tested using a method analogous to ASTM F2413-24 (EH) and CSA Z195-14: determination of resistance to an electric shock, increase 1 kV/sec, voltage 20,000 V/60 Hz holding the voltage for 1 minute. Electrical current requirement below 1.0 mA.

The outsole of the footwear, within specific limits (in the absence of moisture, not referring to the upper), was tested using a method analogous to EN ISO 20345:2022 to provide electrical insulation against voltages up to 1000 V M ohm >1000.

(Test report No. 4351088/E)

DIELECTRIC INSOLE bimaterial extracomfort with activated carbon, breathable, removable, anatomical, absorbent, insulating and antibacterial.

Environmentally Sustainable Eco-Friendly

FO sole resistance to hydrocarbons

E energy absorption on seat region

PS sole resistance to perforation non metallic (nail Ø3,0mm)

HRO resistance to hot contact of the outsole

SR sole resistance against slipping

THIS PRODUCT COMPLIES WITH THE REQUIREMENTS OF THE STANDARD ASTM F2413-24:

- Impact resistant footwear (I)
- Compression resistant footwear (C)
- Puncture Resistant Footwear (PR)
- Electric Hazard Resistant Footwear (EH)
- Slip Resistance (SRO)

Size 39-47 Shoe weight Sz 42 gr. 590



↪ **AREAS OF APPLICATION**

 **Electrician**

↪ **CERTIFICATIONS APPLIED**

 **PS Puncture Resistance with Non-Metallic Insert (nail Ø 3.0mm)**

 **Slip Resistance (mandatory ceramic-Nals test)**

 **ASTM F2413-24**


 **Heel Energy Absorption**

 **Hydrocarbon Resistance**

 **Heat-Resistant Sole 300°C Contact**

 **Insulation up to 20,000V**

↪ **TECHNOLOGIES AND MATERIALS**

 **No metal**

 **Metal-Free**

 **High Breathability**

 **Mondo Point 11**

 **Slip Resistance (optional glycerin test)**

 **Air Tunnel Fabric**

↳ PLUS



Air Tunnel Fabric

Airnet® is a patented technology that ensures maximum foot breathability while wearing robust and abrasion-resistant safety footwear. Thanks to an air tunnel construction, it promotes optimal airflow, and the 100% polyester yarn ensures excellent resistance to abrasion, tensile stress, tearing, and washing.

↳ SOLE

DIELECTRIC Sole line

Dielectric sole line was developed to meet the needs of those working in contact with electrical cables and systems. Specifically, this line offers a safety shoe with an insulating sole that provides specific protection against the risk of electric shock.

This is made possible by a series of insulating materials specifically designed for this purpose: the nitrile rubber compound of the outsole, the polyurethane foam of the midsole, the fabrics of the puncture-resistant insole, and the compound of the internal footbed.

These technologies enabled the shoes to pass electrical resistance tests in accordance with the analogous method of the EN ISO 20344:2021 standard and ASTM F2413 (EH) / CSA Z195-14 at 20 kV/60 Hz.

In addition, the specific materials used in the sole construction allowed the product to obtain the important American certification ASTM 2413-24 EH (Electric Hazard Resistant Footwear).

