

3PU PATENTED

COMING SOON

SUPERNOVA S3L FO SR

3L037CA

CE EN ISO 20345:2022+A1:2024 S3L FO SR ESD

ANKLE SAFETY SHOE

36-49

3CLOUD Elasticity

High safety shoe made of Microfiber Rubber B-tech, thickness 1.8-2.0 mm. Lining in highly breathable and abrasion-resistant fabric. The heel area is reinforced with tear- and abrasion-resistant microfiber, anti-slip, providing stability to the foot during movement. Footwear with reflective fabric insert. Soft padded and lined tongue.

SHOE ENTIRELY METAL FREE.

TOE CAP 200J composite, polymer-based, **non-thermal**, according to EN 22568.

MIDSOLE PL flexible anti-perforation composite fabric, according to EN 22568.

SOLE 3CLOUD triple-density polyurethane, antistatic, resistant to hydrolysis ISO 5423:92, hydrocarbons, and abrasion; anti-shock and slip resistant.

INSOLE YEAH extra comfort insole in closed-cell polyurethane with patented DryGo!® compound.

DryGo!® polyurethane absorbs foot moisture and evaporates it quickly. Thanks to its anatomical, self-molding and resilient properties, it provides long-lasting comfort. Breathable, removable, anatomical, absorbent, antibacterial, and **ESD**.

The footwear meets the requirements according to IEC 61340-4-3:2017 (IEC 61340-5-1:2024) for **ESD** electrical resistance.

FO Sole resistant to hydrocarbons.

SR Slip resistance.










Size: 36-49 **Weight** (size 42): **555g**






→ **AREAS OF APPLICATION**

-  **Construction and Building Sites**
-  **Automotive Components**
-  **ESD Area**
-  **Logistics and Light Industry**
-  **Metal and Wood Carpentry**

→ **CERTIFICATIONS APPLIED**

-  **PL** Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)
-  **ASTM F2413-24**
-  **E** Heel Energy Absorption
-  **SC** Toe Cap Abrasion Resistance
-  **A** Antistatic Footwear
-  **FO** Hydrocarbon Resistance
-  **Slip Resistance** (mandatory ceramic-Nails test)
-  **SRC** Slip Resistant Sole
-  **DGUV 112-191** DGUV 112-191

→ **TECHNOLOGIES AND MATERIALS**

-  **NO METAL** No metal
-  **SR** Slip Resistance (optional glycerin test)
-  **ESD** ESD - Electrostatic Discharge
-  **TECHNICAL TEXTILE** Technical Fabric
-  **MONDO POINT 11** Mondo Point 11
-  **3PU PATENT** Three to be™ - Triple Density Injection

→ **ANTI-SLIP RESULTS**

*after simulation of walking by slight abrasion

Ceramic tile floor with NaLS	Forward Heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward Heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31 ≥ 0.48	≥ 0.36 ≥ 0.50		≥ 0.19 ≥ 0.32	≥ 0.22 ≥ 0.37

↳ PLUS



Three to be™ - Triple Density Injection

Three to Be® - Tripla Densità Iniettata technology represents one of the most advanced results of our R&D efforts. Patented by Giasco, it integrates three entirely polyurethane-injected sole layers to optimize safety shoe performance in terms of comfort, stability, and slip resistance.

↳ SOLE

3CLOUD Elasticity

3Cloud and its distinctive through-holes in the sole have been meticulously designed to provide unique comfort for safety footwear in indoor environments. Specifically, the tunnels running perpendicularly through the midsole offer both a pleasant cushioning effect and high rebound. These features are maintained throughout the entire life of the safety shoe thanks to the polyurethane's strong "memory" property and especially the trapezoidal geometry of the holes. Together, these aspects minimize sole deformation over time. Finally, the outsole of this safety shoe features a dual tread pattern: one inspired by racing tire technology, and the other hexagonal with a "suction cup" effect. Both systems work together to ensure maximum grip on smooth and regular surfaces.

