

## FIREMAN SABF Boots



### Colors

- Black



ATS sole (registered design)      Anti-perforation + Safety toe cap design)

Polymer toe cap\*

Composite anti-perforation mid-sole\*

Outside height (size 8): 370 mm

Weight (size 8): 2100g / pair

Elastomer: fireproofed NBR / CR (fireproofed nitrile/polychloroprene rubber)

### Reference: FIREMAN SABF Boots (safety toe cap + anti-perforation mid-sole)

Excellent resistance to heat flow, heat contact, fire.

Excellent resistance to chemicals : fuels, oils, weak and diluted acids, solvents.

Excellent resistance to abrasion and cuts

Used with chemical protective suits (satisfy permeation tests according to EN 943-1 and EN 943-2).

### Comply with standards :

#### EN 15090 type 3 HI3

Boots for emergency situation and fire with toxic chemicals emission.

#### EN ISO 20345 S5 HRO SRC

- Heel shock absorption.
- Antistatic.
- Resistance to heat contact (HRO).

#### EN 13832-3 J P Q

- Boots highly resistant to chemicals :
- N-Heptane (J)
- Hydrogen peroxide 30% (P)
- Isopropanol (Q)

#### EN 13287

- Sole slip resistance (SRC) :
- Steel floor.
- Ceramic floor.

Marine fire protection equipment certified by BG VERKEHR, notified body N°0736 (only on the model without option).

\* Sizes 3 and 4.5 have steel toe cap and steel midsole.

### Sizes

<b>FR</b>	36	37/38	39	40/41	42	43	44	45	46/47	48	49/50
<b>UK</b>	3	4.5	5.5	7	8	9	9 ½	10 ½	11 ½	13	14

### Available options



**R** : Mid-boot reflective      **AC2** : Leather straps band



www.etcheseurite.com | ZA Ordokia - 64130 VIODOS - ABENSE de BAS - FRANCE | +33 (0)5 59 28 05 41