

FIREMAN SABF RAC2 Boots



Colors

- Black



ATS sole
(registered
design)

Anti-perforation
+ Safety toe cap

Polymer toe cap*

Composite anti-perforation mid-sole*

Outside height (size 8): 330 mm

Weight (size 8): 2100g / pair

Elastomer: fireproofed NBR / CR
(fireproofed
nitrile/polychloroprene rubber)

Reference: FIREMAN SABF RAC2 Boots (safety toe cap + anti-perforation mid-sole)

Excellent resistance to heat flow, heat contact, fire.

Excellent resistance to chemicals : fuels, oils, weak and diluted acids, solvents.

Excellent resistance to abrasion and cuts

Comply with standards :

EN 15090 type 3 HI3

Boots for emergency situation and fire with toxic chemicals emission.

EN ISO 20345 S5 HRO SRC

- Heel shock absorption.
- Antistatic.
- Resistance to heat contact (HRO).

EN 13832-3 J P Q

- Boots highly resistant to chemicals :
- N-Heptane (J)
- Hydrogen peroxide 30% (P)
- Isopropanol (Q)

EN 13287

- Sole slip resistance (SRC) :
- Steel floor.
- Ceramic floor.

Marine fire protection equipment certified by BG VERKEHR, notified body N°0736 (only on the model without option).

* Sizes 3 and 4.5 have steel toe cap and steel midsole.

Sizes

FR	36	37/38	39	40/41	42	43	44	45	46/47	48	49/50
UK	3	4.5	5.5	7	8	9	9 ½	10 ½	11 ½	13	14



www.etcheseurite.com | ZA Ordokia - 64130 VIODOS - ABENSE de BAS - FRANCE | +33 (0)5 59 28 05 41