

HYPALON SA Boots



Colors

- Grey



ATS sole Anti-perforation
(registered + Safety toe cap
design)

Polymer toe cap***

Composite anti-perforation mid-sole***

Microfiber lining OEKO TEX

Outside height for size 8: 370 mm

Weight for size 8: 2200g / pair

Elastomer: CSM (Hypalon ****)

Reference: HYPALON SA Boots (safety toe cap + anti-perforation mid-sole)

Excellent resistance to corrosive chemicals, particularly to concentrated and hot acids, fuels and solvents.

Excellent resistance to abrasion and cuts.

For use with protective clothing in hostile environments.

Comply with standards :

EN ISO 20345:2022 S5S* HRO FO CR LG SR

- Heel energy absorption. Antistatic. Perforation resistant insert (S5)
- Sole perforation resistance to Ø 3 mm nail (S)*
- Contact heat resistance (HRO)
- Fuel oil resistance (FO)
- Cut resistance (CR)
- Sole design and cleats for ladders (LG)

- Sole slip resistance assessed on :
 - - Ceramic floor with sodium lauryl sulfate.
 - Ceramic floor with glycerin (SR).

EN 13832-3** A L R

Footwear protecting against a prolonged contact with chemicals :

- Methanol (A)
- Sulfuric acid 96% (L)
- Sodium Hypochlorite 13% (R)

* "S" marking does not apply to the sizes 3 and 4.5

** Complying with EN 13832-3 : 2018 except for tests performed according to 2022 version of EN ISO 20345 instead of 2011 version.

*** Made of steel for the sizes 3 and 4.5

**** DuPont Performance Elastomer patented

Sizes

FR	36	37/38	39	40/41	42	43	44	45	46/47	48	49/50
UK	3	4.5	5.5	7	8	9	9 ½	10 ½	11 ½	13	14



www.etcheseurite.com | ZA Ordokia - 64130 VIODOS - ABENSE de BAS - FRANCE | +33 (0)5 59 28 05 41